

**NAME**

`gxl2gv`, `gv2gxl` – GXL-GV converters

**SYNOPSIS**

**`gxl2gv`** [ **`-gd?`** ] [ **`-ooutfile`** ] [ *files* ]

**`gv2gxl`** [ **`-gd?`** ] [ **`-ooutfile`** ] [ *files* ]

**DESCRIPTION**

**`gxl2gv`** converts between graphs represented in GXL and in the GV language. Unless a conversion type is specified using a flag, **`gxl2gv`** will deduce the type of conversion from the suffix of the input file, a ".gv" suffix causing a conversion from GV to GXL, and a ".gxl" suffix causing a conversion from GXL to GV. If no suffix is available, e.g. when the input is from a pipe, and no flags are used then **`gxl2gv`** assumes the type of the input file from its executable name so that **`gxl2gv`** converts from GXL to GV, and **`gv2gxl`** converts from GV to GXL.

GXL supports a much richer graph model than GV. **`gxl2gv`** will attempt to map GXL constructs into the analogous GV construct when this is possible. If not, the GXL information is stored as an attribute. The intention is that applying **`gxl2gv|gv2gxl`** is semantically equivalent to the identity operator.

**OPTIONS**

The following options are supported:

**`-g`** The command name and input file extensions are ignored, the input is taken as a GV file and a GXL file is generated.

**`-d`** The command name and input file extensions are ignored, the input is taken as a GXL file and a GV file is generated.

**`-?`** Prints usage information and exits.

**`-o outfile`**

If specified, the output will be written into the file *outfile*. Otherwise, output is written to standard out.

**OPERANDS**

The following operand is supported:

*files* Names of files containing 1 or more graphs in GXL or GV. If no *files* operand is specified, the standard input will be used.

**RETURN CODES**

Both **`gxl2gv`** and **`gv2gxl`** return **0** if there were no problems during conversion; and non-zero if any error occurred.

**BUGS**

**`gxl2gv`** will only convert in one direction even if given multiple files with varying suffixes.

The conversion can only handle one graph per GXL file.

There are some GXL constructs which **`gxl2gv`** cannot handle.

**AUTHORS**

Krishnam Pericherla <kp@research.att.com>

Emden R. Gansner <erg@research.att.com>

**SEE ALSO**

`dot(1)`, `neato(1)`, `twopi(1)`